

NORTON

STAGE MONITOR | **NF8**

Norton[®]
audio

STAGE MONITOR | NF8



With optimal vocal intelligibility and exceptionally regular response in frequency and time, NF8 is a stand-alone plug and play Coaxial two way passive device with single Point-Source acoustic radiation in a very compact and low profile footprint.

Containing a 1.5" silk-diaphragm driver coaxially loaded by an 8" low frequency loudspeaker in a bass-reflex tuned enclosure, the NF8 is a high fidelity and high output element that delivers incredible Spl from such a small enclosure.

The high-frequency driver is a remarkable device that incorporates the last and most innovative technologies, achieving a size so compact that allows it to be assembled at the exact 8" loudspeaker acoustic origin.

The NF8 loudspeaker, due to their small size, is also recommended in all situations in where it is mandatory an visually non-obstructive sound reinforcement system.

The NF8 will be very well accepted in where great sound quality and little space occupancy are a must.

Usable Bandwidth (- 10 dB): 85 Hz – 20 KHz
Nominal Directivity (- 6 dB): 90° Conical
SPL 1W/1m: 94 dB
Maximum Continuous SPL: 118 dB
Power: 300 W

Components:

- LF: 1 x 8" Weather-resistant 8 ohm
- HF: 1 x 1,5" HF Silk-diaphragm driver 8 ohm

Rigging: 6 points M6 T Nuts 1 Top hat

Physical Data:

- Width: 400 mm
- Height: 252,7 mm
- Depth: 310,9 mm
- Weight: 10 Kg
- Material: Baltic Birch Plywood
- Connections: 2 x 4 Pin Speakon

